




FOS 100 DYNAMIC SOLO FC

LED BAR WITH SINGLE PIXEL CONTROL TO CREATE AN ENDLESS VARIETY OF DYNAMIC EFFECTS

FOS 100 DYNAMIC is a **compact and robust LED bar** fitted with 15 OSTAR Full Color LEDs individually controllable. This powerful LED bar **can be used either for background lighting or for dynamic effects**. The unit is available with **different beam angles** and it can be fitted with additional filters to further enlarge its projections range. FOS 100 DYNAMIC SOLO is available with **integrated IP20 PSU** for temporary installation or with **IP65 PSU** for permanent ones.



- LED
- FC Full Color
- Lens Sets
- IP20
- built-in PSU
- RDM/DMX
- 10° +40°



SP LENS 10°
03.DYN008S.F10

MF LENS 25°
03.DYN008S.F25

WF LENS 40°
03.DYN008S.F40

OUTPUT

- 15 Full Color (RGBW) LEDs
- Pixel to pixel control
- Lumens: 4,608 @ 500mA
- LED lifespan: 50,000 hours (70% lumen output)

OPTICAL GROUP

- 3 lenses sets available: 10° / 25° / 40°
- Holographic filters available on request
- Uniform projection on surfaces

COLOR GENERATION

- 16 million colors
- Wide palette of pure uniform whites with variable linear color temperature (2700K - 8000K)

CONTROL

- DMX 512 / RDM
- 4-digit 7-segment LED display + 4 soft keys
- Internal operating system updatable via DTS dongle firmware uploader

DMX

- 10 DMX channels (default)

POWER SUPPLY

- Integrated Full-range PSU 100-240Vac 50-60 Hz
- Available with IP65 PSU for permanent installations
- Power consumption: 150 W Max

CONNECTIONS

- PowerCON IN/OUT panel connectors
- XLR 5 pins IN/OUT panel connectors

OPERATING TEMPERATURE

-10° / 40° C

PHYSICAL

- IP20
- Housing: Aluminium
- Weight: 6.5 Kg (14.3 lbs)
- Finishing: Black

SHIPPING

- Packaging: Carton box
- Box size: 1060 x 200 x 200 mm (41.7" x 7.9" x 7.9")
- Box weight: 7.9 Kg (17.4 lbs)

ACCESSORIES INCLUDED

- 1 x Fit joint for joining bars inline (code 02M09519.46)
- 2 x M4 knob for fit joint (code 0511P014)
- 1 x PowerCON IN female cable connector (code 0520P014)
- 1 x PowerCON OUT female cable connector (code 0520P029)
- 1 x XLR 5 Pins female cable connector (code 0508B027)
- 1 x XLR 5 Pins male cable connector (code 0508B028)

ACCESSORIES ON REQUEST

- Lenses set Narrow 10° (code 03.LK.060.N)
- Lenses set Medium 25° (code 03.LK.061.N)
- Lenses set Wide 40° (code 03.LK.062.N)
- Barndoor and Holographic Filter holder (code 03.LA.142)
- Kit Fit joint for joining bars inline (code 03.LA.023)
- Fast-lock bracket kit (code 03.LA.024)
- Short bracket for wall installation (code 03.LA.025)
- Single-side light shield (code 02M09594.46)
- "Fast Lock" omega bracket with connection 1/4 turn (code 02K00467)
- G60 "C" Clamp - max. load 50 Kg (code 0521A004)
- Flightcase for 4 units (code 0521C039.1)
- DTS dongle firmware uploader (code 03.LA.206)

PHOTOMETRIC DATA

	mt 3 ft 9.84	mt 6 ft 19.68	mt 9 ft 29.53	mt 12 ft 39.37	mt 15 ft 49.21
BEAM ANGLE 10°					
lux center (lx)	3687	922	410	230	147
foot candles (fc)	343	86	38	21	14
diameter (cm)	52	105	157	210	262
diameter (ft)	1.72	3.44	5.17	6.89	8.61
BEAM ANGLE 25°					
	mt 3 ft 9.84	mt 6 ft 19.68	mt 9 ft 29.53	mt 12 ft 39.37	mt 15 ft 49.21
lux center (lx)	1402	351	156	88	56
foot candles (fc)	130	33	14	8	5
diameter (cm)	133	266	399	532	665
diameter (ft)	4.36	8.73	13.09	17.46	21.82
BEAM ANGLE 40°					
	mt 3 ft 9.84	mt 6 ft 19.68	mt 9 ft 29.53	mt 12 ft 39.37	mt 15 ft 49.21
lux center (lx)	950	238	106	59	38
foot candles (fc)	88	22	10	6	4
diameter (cm)	218	437	655	874	1092
diameter (ft)	7.16	14.33	21.49	28.66	35.82